

TRANSPORT TRAILER FOR PORTABLE TOILETS

GLOBAL EXPRESS 12



TRANSPORT TRAILER WITH 2-AXLE CHASSIS, DRAWBAR AND OVERRUN COUPLING

SPECIFICATIONS

Number of axles	2
Loading length ca.	7100 mm
Loading width ca.	2400 mm
Loading height ca.	680 mm
Total length ca.	8600 mm
Total width ca.	2400 mm
Total height (unladen) ca.	1850 mm
Gross vehicle weight	3500 kg
Payload	2000 kg
Hot-dip galvanized profiled steel frame	
Car electrics	
13-pole connector	
Wheels 195/50 R13	
4 support legs with crank handle	
Brake shoes	

Brake shoes

Toilets must be completely secured with cargo straps for transportation.







Large transport trailer for 12 portable toilets. The trailer features a lightweight aluminum platform on two axles, which ensures maximum durability and easy maneuverability.

A professional load securing system is provided by the longitudinal center bar, the crossbar at the front, two crossbars after 3 cabins and another after 2 cabins, all with double lashing eyes.

The rear part of the continuous loading area can be used for either two cabins, a handicap cabin (overhang) or other purposes.

This transport trailer is suitable for all portable toilets on the market.



LAYOUT STANDARD

GLOBAL EXPRESS 12



