

TRANSPORT TRAILER FOR PORTABLE TOILETS

## **GLOBAL EXPRESS 2**



## TRANSPORT TRAILER WITH SINGLE-AXLE CHASSIS WITH TUBULAR DRAWBAR AND BALL COUPLING

## **SPECIFICATIONS**

for transportation.

| Number of axles                         | 1        |
|---|----------|
| Loading length ca.                      | 2x1300mm |
| Loading width ca.                       | 1460 mm  |
| Loading height ca.                      | 480 mm   |
| Total length ca.                        | 4285 mm  |
| Total width ca.                         | 2310 mm  |
| Total height (unladen) ca.              | 1850 mm  |
| Gross vehicle weight                    | 750 kg   |
| Payload                                 | 370 kg   |
| Hot-dip galvanized profiled steel frame |          |
| Car electrics                           |          |
| 13-pole connector                       |          |
| Wheels 195/50 R13                       |          |
| 4 support legs with crank handle        |          |
| Brake shoes                             |          |

Toilets must be completely secured with cargo straps









The GLOBAL Express 2 is the ideal solution for transporting and using two GLOBAL portable toilets of the types FOCUS, MTM or POLAR on site.

It offers convenient access to the cabins via two steps on one side, while the integrated handrail mounting rack ensures increased safety during use.

The robust single-axle chassis with tubular drawbar and ball coupling guarantees easy connection to the towing vehicle and ensures easy maneuverability. The construction is made of a hot-dip galvanized steel profile frame with aluminum panels and promises not only high resistance to weather influences, but also a long service life.



LAYOUT STANDARD

## **GLOBAL EXPRESS 2**





