

VACUUM SERVICE UNITS

GLOBAL FLX 1000 PICK-UP



CAN ONLY BE MOUNTED ON A PICK-UP TRUCK CARRYING A SINGLE CAB

SPECIFICATIONS

Total volume	ca. 10001
Waste water	ca. 6001
Fresh water	ca. 4001
Tank diameter	ca. 1000 mm
Length (top)	1475 mm
Width (top)	1661 mm
Height (top)	1375 mm
Length (between wheel arches)	1250 mm
Width (between wheel arches)	970 mm
Height (between wheel arches)	497 mm
Weight	ca. 480 kg
Galvanized two-chamber waste water water inner tube	er tank with fresh
Vacuum numn MEC 1600 P	

Vacuum pump MEC 1600 P

High-pressure cleaner

The unit stands on a fully galvanized steel frame that can be moved by forklift.



This galvanized steel tank, inside as well as outside, has an inner tube for the fresh water. The compact construction fits on the loading area of a pickup truck (Ranger, Dodge, or similar) with a single cab. There must be a payload of at least 1000 kg.

Further FLX units with larger tanks up to 3400 liters available on request.

EQUIPMENT

Inside and outside galvanized waste water tank, MEC 1600P vacuum pump, Honda GX 390 engine, swing-mounted machine plate, 9.1m suction hose, lance with ball valve, level indicator for all tanks, lightweight aluminum construction, emergency stop switch

OPTIONAL EQUIPMENT

High-pressure cleaner with 20-meter hose on a hose reel, position of the machine plate on the front side, suction hose in different lengths, tool box

